DETECTO





Install the 7550 Right in High-Traffic Areas and Fold Up When Done Weighing



- floor space
- The wall-mount scale stores easily out of the way and aesthetically blends into any environment for a more efficient workflow
- included standard for wireless connectivity with EMR/EHR systems
- Sturdy steel construction for long-lasting durability over a lifetime of use

Integrated full-color, touchscreen LCD with wheelchair tare weight mode to remove wheelchair weights and factor patient weight





Mounts Securely to the Wall for Storage

- 36 in W x 33 in D / 91 cm W x 84 cm D Weighing Platform Provides Ample Room
- Wheelchair Tare Entry Can be Done Before or After the Patient is on the Scale
- Accommodates Some Sizes of **Power Wheelchairs**
- May be Used on Carpet or Hard Floor Surfaces
- Wi-Fi and Bluetooth 5.0 Wireless Connectivity
- 6 C Batteries (not included) or AC Adapter (included on some models)
- Body Mass Index Calculation
- Units Locking into LB or KG
- Two-Way Easy Access Ramps
- Auto Weight Lock Feature
- Gas Spring Platform Lifting Mechanism
- StableSENSE Adjustable Filtering
- Textured Non-Skid Mat on Ramp and Platform
- Compact Vertical Fold-Up Platform Conserves Space
- Pushbutton and Keypad Tare for Wheelchair Weights

8-Digit Numeric Patient ID

DETECTO's 7550 incorporates an iPhone-like touchscreen LCD that allows you to enter up to 8-digit patient IDs that can be sent along with patient weight data to EMR systems via Wi-Fi or Bluetooth 5.0.









Detecto's model 7550 wheelchair scale features a unique fold-up storage design that saves space when not in use. The 7550 easily accommodates most wheelchairs, and yet requires very little floor space when folded up. The slim 7-inch / 18-cm profile takes up minimal space when installed in a medical facility hallway, clinical office, long-term care center, or nursing home.

When you're ready to weigh, simply lower the platform and the gas spring lifting mechanism will gently lower it into place. The 7550's 1.5-inch/38-mm high platform is very low to the ground for easy patient access. This makes the process simple and minimal effort required in order to roll a patient on and off the weighing platform.



7550

WALL-MOUNT FOLD-UP









| | 7550 | 7550-AC | 7550KGEU |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------|-----------------|
| Capacity | 1,000 lb x 0.2 lb | / 450 kg x 0.1 kg | 300 kg x 0.1 kg |
| AC Adapter | | • | |
| OIML EC Class III | | | M |
| Platform Size (Flat Portion) | 36 in W x 33 in D / 91 cm W x 84 cm D | | |
| Width | 50.3 in / 127.6 cm | | |
| Depth | 39.3 in / 99.7 cm (with platform extended); 7.3 in / 18.4 cm (without platform extended) | | |
| Overall Height | 44.0 in / 111.7 cm | | |
| Display Type | 3.2 in (diagonal) full color TFT display, 320 x 240 resolution | | |
| Number of Characters | Weight: 5 digits, 0.8 in (20 mm) high | | |
| | Height: 4 digits, 0.35 in (9 mm) high | | |
| | BMI: 3 digits, 0.35 in (9 mm) high | | |
| Keys | Mechanical switch type, Power, Zero, Lock/Release, ID, Cycle Display Mode, Menu, Print | | |
| Power Requirements | Six C size Alkaline, Ni-Cad, or NiMH batteries (not included) | | |
| | Domestic models: Optional 100 to 240V AC 50/60Hz 12V DC 1A wall plug-in UL/CSA listed AC power adapter (Cardinal part number 6800-1045) | | |
| | International models: Optional 100 to 240V AC 50/60Hz 12V DC 1A Multi-Pin Input AC power adapter (Cardinal part number 6800-1047) | | |
| Operating Environment | Operating Temperature Range: 14 to 104 °F (-10 to +40 °C), Humidity: 0 to 90% non- condensing | | |
| Communication Interfaces | Wi-Fi and Bluetooth 5.0 | | |
| Construction | Steel | | |
| Weighing Mechanism | Electronic load cells | | |
| Lifting Mechanism | Gas springs | | |
| Net Weight | 180 lb / 82 kg | 181 lb / 83 kg | 180 lb / 82 kg |
| Shipping Weight | 238 lb / 108 kg | 239 lb / 109 kg | 238 lb / 108 kg |

DETECTO reserves the right to improve, enhance, or modify features and specifications without prior notice.

DETECTO

102 East Daugherty St., Webb City, MO 64870 USA Toll-Free: (800) 641-2008 E-mail: detecto@cardet.com www.Detecto.com **SOLD BY:**